

COUPON FOR MEASURING CORROSION RATES AND SYSTEM

Brief Description of the Invention

- 5 This invention relates generally to a coupon for measuring corrosion rates in hostile environments, to a corrosion rate measuring system employing a probe for placing the coupon in the hostile environment, and to a system for monitoring the corrosion of said coupon when it is placed in the hostile environment.

Background of the Invention

- 10 Various attempts have been made to measure in real-time the corrosion rates of metals exposed to extremely high temperatures in hostile environments, such as those present in a coal-fired boiler. Specifically, the inner wall surfaces of a typical steam boiler are lined with tubes that carry water that, by virtue of the heat released within
- 15 the boiler from the burning of a suitable fuel, is converted into steam. The metals from which boiler tubes are made are subject to corrosion in this environment and, over a period of time, these tubes can fail from surface corrosion. While temperatures within the boiler can exceed 3000°F, the surfaces of these tubes are typically at about 800°F.
- 20 In the past, devices have been developed that can be inserted through the boiler wall so as to expose a metal coupon to this "fireside" environment. Passive and active systems have been developed and some are commercially available. Passive systems typically expose a sample of boiler tube material to the fireside environment, while the sample is cooled and maintained at a temperature (around 800°F) representative of the
- 25 tube metal surface temperature. After a predetermined time, the probe and coupon are removed and the coupon is retrieved and analyzed to determine the rate of corrosion.

In some passive systems, the coupons are prepared so that part of the surface exposed to fireside conditions is coated with a metal that is essentially inert to corrosion, while the other part of the coupon is directly exposed to the fireside environment. These types of coupons work well and have been used to determine corrosion rates. While
5 this method will allow for the determination of a corrosion rate, it only provides this rate after being exposed for some period of time and can provide no immediate warning of failure due to a change in operating conditions or fuel.

Active systems that measure corrosion rates have been developed as well, and are commercially available. While these systems employ different methods to
10 measure real-time rates of corrosion, all such measurements must rely on the loss of material to provide such measurements. One common approach is to measure the change in electrical resistance of a sample while it corrodes. Increasing resistance correlates to loss of material and with proper correction for those parameters that can affect the proper measurement of resistance (temperature, in particular) a corrosion
15 rate can be determined from the accurate measurement of the change in resistance of a coupon compared to some standard. Unfortunately, these systems are typically not suitable for use in such a hostile, hot environment as that found within a boiler where it is difficult to maintain a corrosion coupon at a uniform temperature while making a measurement of the resistance of the coupon. In addition, because a macroscopic
20 coupon will increase in resistance (corrode) at a very slow rate, very small changes in resistance must be measured in order to determine a corrosion rate. This is a considerable technical challenge, given the fireside environment.

One such active system uses an electrically isolated thin steel coupon (~0.25 mm thick) positioned in the end of an air-cooled probe. A thermocouple is attached to
25 an indentation in the rear side of this coupon for monitoring and controlling temperature. In the fireside environment, the coupon is maintained at 800°F. To measure the resistance of the coupon, a large current (10A) is periodically passed through the coupon and an external standard resistance. While the current is maintained (for about 1 second), the voltage drop across the coupon and the external
30 standard resistor is measured and recorded. Large currents are required because, although the coupon is small (about 50 mm across), its electrical resistance is low. Changes in the resistance of the coupon over time, when compared to the external standard resistor, are used to infer the corrosion rate.

This device suffers from a number of conceptual as well as practical difficulties. Corrosion rate is derived from the rate of loss of a section of the sensor coupon as inferred from changes in its electrical resistance. This approach assumes that the sensor coupon is thinned uniformly along its entire length, which implies that the temperature of the sensor coupon is uniform throughout and/or is accurately known. It also limits the technique to measuring corrosion rates where the mode of attack is uniform; pitting attack cannot be readily measured. A major practical problem is that, because of the high, variable heat fluxes typical of fireside conditions, it is very difficult to control the temperature of the coupon surface to a preset value.

The resistance of the coupon is low, whereby changes in resistance due to corrosion are small, making them difficult to measure. Even slight temperature variations result in significant changes in resistance compared to the changes due to corrosion, thus making the precise measurement of the resistance of the coupon difficult, if not impossible. The fact that the variations are dynamic rather than static represents another considerable obstacle to the success of this approach. The large currents that are employed tend to heat the standard or reference resistor as well as the coupon, and thereby add uncertainty to the measurement of resistance. The fact that the coupon must be electrically isolated from the rest of the probe increases the complexity of the device. Because the change in resistance is small, measurements are not only affected by temperature variations, but they are also affected by electrical transients.

Summary of the Invention

The present invention provides a coupon which employs two or more thin-film, high-resistance metal elements carried on a substrate with one or more elements exposed to the corrosive environment while at least one element is protected from the corrosive effects of the hostile environment to provide a reference. Being mounted in close physical proximity on the same substrate, the elements are subjected to essentially the same corrosive environment, so that the effect of varying temperature is experienced by all of the elements. The advantage of high resistance is that only a small current is required to produce a large voltage drop for the measurement of resistance. Corrosion of the thin film corrosion element yields a significant change in resistance, providing the capability of quickly measuring dynamically varying rates of corrosion.

Brief Description of the Drawings

The foregoing and other objects of the invention will be more clearly understood from the following description when read in conjunction with the accompanying drawings in which:

- 5 Figure 1 is a top plan view of a coupon in accordance with the present invention, showing the corroding thin film resistance element.

Figure 2 is a bottom plan view of the coupon of Figure 1 showing the thin film resistance reference element.

Figure 3 is a sectional view taken along the line 3-3 of Figure 1.

- 10 Figure 4 is a top plan view of a coupon in accordance with another embodiment of the invention.

Figure 5 is a sectional view along the line 5-5 of Figure 4.

Figure 6 is a top plan view of a coupon in accordance with still another embodiment of the present invention.

- 15 Figure 7 is a top plan view of a coupon in accordance with a further embodiment of the present invention.

Figure 8 is a sectional view showing a coupon mounted on a corrosion probe.

Figure 9 is a sectional view showing a coupon mounted on a hollow bolt.

- 20 Figure 10 is a circuit diagram of a circuit for measuring the change in resistance due to corrosion.

Figure 11 is a curve showing the change in resistance due to corrosion, illustrating two corrosion rates.

Description of the Preferred Embodiment

- 25 Thin film corrosion elements of constant cross-section are deposited on a substrate that is electrically non-conductive or is treated to have an electrically non-conductive surface film. Small rates of corrosion of the film exposed to the hostile environment will yield a large change in its resistance.

- 30 The thin film corrosion elements are fabricated in one of two ways, either of which will withstand the fireside environment. In either approach, thin films of the metal of interest (for instance, iron) are sputtered or evaporated onto electrically insulating substrates. In one embodiment, two patterns are applied or deposited onto a substrate. One pattern is covered by a film of inert material, whereby it is protected

from the corrosive environment, while the other thin film pattern is exposed to the corrosive environment. The two thin patterns are positioned so that they will be subjected to substantially the same temperature environment.

5 In another embodiment, the patterns are deposited on opposite sides of a thin substrate, whereby only one pattern is exposed to the hostile environment. The side of the coupon not exposed to the hostile environment may or may not need to be protected by a protective layer. In another embodiment, both patterns are on the same side of the substrate and overlying one another, with one pattern protected by a corrosion-resistant layer and insulated from the top exposed pattern.

10 Referring now to Figures 1-3, a coupon which includes elongated thin metal conductors 11 and 12 on opposite surfaces of a disc-shaped substrate 13 is shown. The substrate may comprise a thin wafer of beryllium oxide ceramic (beryllia). While any suitable ceramic can be adapted, it appears that beryllia offers the best properties because it is an excellent electrical insulator, is easily formed into thin sheets, is
15 chemically inert in a fireside environment, has a heat conductivity near that of steel, and has a coefficient of thermal expansion which is high enough to preclude the spalling or peeling off of films sputtered onto its surface.

Another suitable substrate is the metal alloy FeCrAlY. This alloy has the desired property that when it is heated to 2012°F (1100°C) in air and maintained at
20 that temperature for a period of time, a very adherent, electrically-insulating, hard, thin film of alpha-alumina grows on its surface. Other substrates, such as glass, can be used for lower temperature applications.

The thin metal conductive elements can be formed employing deposition techniques known in the semiconductor processing art. Thin film elements having
25 substantially uniform cross-sectional areas can be formed by masking the surface of the substrate 13 by photolithographic methods, forming openings in the mask conforming to the desired configuration of the resistive elements, and then depositing by sputtering or other deposition technique a thin film of metal onto the surface of the mask. The metal adheres to the substrate in the windows or openings. When metal of
30 desired thickness has been deposited, the deposition process is terminated, and the mask is removed by dissolving or etching, leaving the conductive pattern.

In the example of Figure 1, thin film spiral metal conductors 11 and 12 are formed. The connection to the center of the spiral is made by masking and depositing

metal to form a radial conductive lead 14. This is followed by masking and depositing a suitable oxide film 16 over the conductor to protect the conductive lead 14 from the hostile environment, and electrically insulate the lead from the overlying spiral conductor to which it is connected. Finally, by masking and depositing metal, the spiral is formed with voltage and current connections 17, 18 and 19, 20, respectively. A similar process is carried out to form spiral conductor 12 on the underside of the substrate directly opposite the upper spiral. The spiral includes voltage and current connectors 22, 23 and 24, 25, respectively. Since the substrate is thermally thin, the two resistive elements 11 and 12 are exposed to substantially the same thermal environment. The conductive film on the lower surface is preferably overcoated with a protective sputtered-on oxide layer 27 to prevent corrosion.

The details of which metal to use for the thin film sensor are thought to be readily resolvable, even though it is unlikely that deposition techniques can produce the exact alloy composition (or microstructure) used for the actual components for which the corrosion rate data are desired. There is, however, sufficient understanding of the corrosion behavior of various alloy systems to allow correlation to be made between the corrosion rate of, for instance, pure iron (which could be deposited on a probe) and carbon steels that are commonly used for heat transfer tubing which is subjected to the hostile environment. Electrical connection can be made to the terminals 17, 18 and 19, 20 at the end of the spiral 11 through the substrate by providing holes in the substrate into which conductive material is deposited during the deposition of the thin film conductor. Electrical connections can be directly made to the terminals 22, 23 and 24, 25 on the spiral 12 formed on the other surface of the wafer.

In a more complex embodiment, Figures 4 and 5, the two conductive elements 31 and 32, are on the same side of an appropriate substrate material 33. They are separated by a protective oxide layer 34 that keeps the underside element 32 from experiencing corrosion. The element is subjected to exactly the same thermal environment as the upper corroding element 31. As in Figure 1, masking is used to create a pathway underneath each spiral. The essential technology is that of multilayer deposition by sputtering through multiple masks. The spiral 32 is formed on the upper surface of the substrate 33, as in Figure 1. The protective oxide layer 34 is then formed. The upper element 31 is formed after rotating the substrate by 90° to allow

for proper placement of the connection pads 36, 37 and 38, 39 for current and voltage measurement. The lower, noncorroding spiral is overcoated with the protective sputtered-on oxide layer 34. The idea is that the non-corroding layer is placed directly underneath the reacting layer on the same side of the substrate as the corroding layer.

- 5 Thus, the substrate need not be thin to maintain substantially equal temperatures on the two sides, because both resistive elements will experience the same thermal environment.

Figure 6 illustrates another configuration for a single-sided corroding and non-
corroding coupon. The layouts do not explicitly require the layers to be stacked upon
10 one another, rather the concept is that they are so close throughout their paths that they experience substantially the same thermal environment.

The coupon includes a substrate 41 on which are formed metal elements 42 and 43. The element 43 is protected by an oxide film 44. The ends of the elements include voltage and current connection pads 46. Figure 7 shows an embodiment
15 including two corroding elements 42a and 42b laid down in connection with one protected element 43, thereby providing two real-time measurements of corrosion rate, while being referred to a single non-corroding protective metal layer. In all embodiments, connections to the various metal layers or elements are provided by depositing metal conductive material into holes formed in the substrate or by leads
20 extending through the holes. If the substrate is a metal substrate which has been treated to form protective oxide film, holes are formed before oxidation so that an insulating oxide covers the walls of the holes. Metal leads can extend through the holes without shorting to the metal substrate. It should be apparent that other configurations for the thin film elements may be employed. The elements should
25 provide a continuous high resistance path in which there is a substantial change in resistance as the element corrodes.

Referring to Figure 8, a coupon 51, formed in accordance with one of the embodiments discussed above, is secured to the end of the hollow probe 52 by means of a ring 53 which is threaded onto the end 54 of the hollow probe. A concentric tube
30 56 is suitably mounted within the probe 52, and provides for directing the flow of cooling air 57 through the tube 56 to the underside ⁵¹57 of the coupon. The flow of air is controlled to maintain the coupon at substantially the same temperature as the metal

whose corrosion is to be measured. Leads 59 are shown connected to the metal films of the coupon.

In another embodiment, Figure 9, a coupon 60 can be mounted at the end of a bolt 61 by a ring 62 threaded onto the end of the bolt. The bolt can be directly threaded by threads 63 into the wall of the boiler, whereby it is maintained at substantially the same temperature as the boiler tubes. There would be no necessity for cooling.

Figure 10 is a diagram of a circuit suitable for measuring the change in resistance of the corrosion element. R_C represents the resistance of the corroding element while R_R represents the resistance of the reference elements. A current I is caused to flow through the two elements. The voltage V_C and V_R across the two elements is applied to a circuit 71 configured to receive the current I and the voltages V_C and V_R and calculate the change in resistance ΔR due to corrosion, as follows:

$$\Delta R = R_C - R_R = \frac{V_C}{I} - \frac{V_R}{I}.$$

It is apparent that other means of measuring the change in resistance using alternating or dc current are available. For example, measuring the voltage drop across the resistive elements with a volt meter or lock-in amplifier.

Figure 11 schematically illustrates the change in resistance with corrosion. Curve A shows a constant corrosion rate and curve B a corrosion rate which is increasing rapidly, signaling a potentially dangerous condition. The actual amount of corrosion can be easily calculated knowing the composition of the thin film material and the boiler tube material.

As described above, the material selected for the corrosion element should preferably be one that corrodes at substantially the same rate as the tubing or other component which is being monitored or in the alternative one for which a relationship can be calculated. The circuit can be calibrated to provide an indication of the amount of corrosion.

The corrosion elements can be made very thin and long to provide a high resistance whereby corrosion will have a large effect upon the resistance. This, coupled with the fact that the reference and corrosion elements are in close proximity,

whereby they are subjected to the same temperature, provides a highly sensitive corrosion measuring coupon and system.

The foregoing descriptions of specific embodiments of the present invention are presented for the purposes of illustration and description. They are not intended to
5 be exhaustive or to limit the invention to the precise forms disclosed; obviously many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as are
10 suited to the particular use contemplated. It is intended that the scope of the invention be defined by the following claims and their equivalents.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
221